

# FLASHING BAND 300/390

## TECHNICAL DATA SHEET

### MATERIAL / APPLICATION

Aluminium self-adhesive flashing band, used for the waterproofing of chimneys and wall abutments, as well as other sensitive roof details where reliable waterproofing is needed.

Highly innovative solution, combining high flexibility and 25% stretchability with butyl-based excellent gluing performance.

Made with UV-stabilized coated aluminium, it has a high resistance to all weather conditions.

### TECHNICAL CHARACTERISTICS

Thickness of the aluminum	100 µ
Density of butyl glue	1,7 g/m <sup>3</sup>
Width of butyl glue	290 mm +/- 1 mm
Thickness of butyl glue	1,0 mm +/- 0,1 mm
Minimum installation temperature	+5 °C
Temperature resistance	from -30 °C to +80 °C

### PACKAGING

	FLASHING BAND 300	FLASHING BAND 390*
Size roll	30 cm x 2,5 m	39 cm x 2,5 m
Weight roll	1,5 kg	1,9 kg
Grouping box	4 rolls	4 rolls
Quantity per pallet	360 rolls	240 rolls

\* For high profile clay tiles. Available with Terracotta color only.

6 standard colours:

- Onduline Red (RAL 8015)
- Brick Red (RAL 3013)
- Terracotta (RAL 8004)
- Brown (RAL 8019)
- Black (RAL 9005)
- Grey (RAL 7021)

### HANDLING AND STORAGE

The product should be protected from direct sunlight and be stored dry.



### INSTALLATION

FLASHING BAND 300/390 is cold applied. The surfaces to be sealed have to be dry. Free from frost, grease and silicone as well as abrasion-proof. The best application temperature range is above +5 °C. FLASHING BAND 300/390 has to be pressed on firmly after the application. The appearance of cavities (blisters) has to be avoided.

If several tapes will be applied the overlapping has to be at least 50 mm.

For chimney and wall abutments, secure long term waterproofing by finishing upper edge of FLASHING BAND 300/390 with a Z-profile and a strip of silicone mastic.

### WARRANTY

Product durability is guaranteed for 10 years. Color stability is guaranteed for 3 years.

All the claims will be considered with respect to application recommendations issued by Onduline company.

This TDS was made based on currently available information. Product was made in accordance with above mentioned parameters but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company.

[www.onduline.com](http://www.onduline.com)

Onduline  
35, rue Baudin  
92300 Levallois-Perret, FRANCE

02/2016

**Onduline**®