

ONDUVILLA® APRON PIECE

TECHNICAL DATA SHEET

APPLICATION

The APRON PIECE is mainly used in the ridge system of ONDUVILLA®, to secure appropriate watertightness and ventilation of the ridge line

Designed as a multi purpose element, it is also used:

- as a junction element between ONDUVILLA® tiles and vertical wall abutment
- in the case of a slope change (as an alternative to our sealing tape FLASHING BAND).

TECHNICAL CHARACTERISTICS

Made of cellulosic fibers, natural pigments and bitumen.
Manufactured using molding process (patented technology).

Length	102 cm
Width	14 cm
Height of corrugation	4 cm
Thickness	2,2 mm
Weight (pigmented/painted)	0,36 / 0,38 kg

PACKAGING

Full range matching all ONDUVILLA® colours (pigmented/painted).
Box 20 pcs
Pallet 28 boxes (560 pcs)

HANDLING AND STORAGE

The product should be protected from direct sunlight and be stored dry.

INSTALLATION

Used at ridge for roofs with a pitch up to 120% (50°). For pitches between 70% and 120%, it is necessary to cut the flat part above the corrugations.

A gap of 1 cm is necessary between both APRON PIECES, in order to ensure appropriate ventilation.

When used as a wall abutment, the ventilation gap between the wall and the APRON PIECE is also necessary. Watertightness is secured by using an aluminium Z-profile and a line of silicon mastic.


For specific roof details, please refer to ONDUVILLA® fixing guide.

This TDS was made based on currently available information. Product was made in accordance with above mentioned parameters but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company.

www.onduline.com

Onduline
35, rue Baudin
92300 Levallois-Perret, FRANCE

08/2016



WARRANTY

Watertightness is guaranteed for 15 years.

All the claims will be considered with respect to application recommendations issued by Onduline company.

Onduline®