

ONDULAIR SLIM

TECHNICAL DATA SHEET

MATERIAL / APPLICATION

ONDULAIR SLIM is a sealing tape which is designed to combine excellent waterproofing and ventilation properties.

Slim size (width 15 cm) makes it compatible with the use of the Slim cap, the ridge accessory of ONDUVILLA® Roofing System, offering ultimate aesthetics to the roof.

It will provide an efficient complement of ventilation at hips in Residential applications, where the draining of water vapor is essential.

It can also be used at ridge, in non-residential applications (roof surface < 20 m²).

ONDULAIR SLIM is made of lacquered, UV resistant, single-layer aluminum.

The size of the vents also ensures good protection against insects.

TECHNICAL CHARACTERISTICS

Width	150 mm
Thickness of the aluminum	140 µ
Free area for ventilation	32,5 cm ² per linear meter
Density of butyl glue	1,7 g/m ³
Standard width of butyl glue	15 mm +/- 1 mm
Minimum installation temperature	+5 °C
Temperature resistance from	-30 °C to +80 °C

PACKAGING

- Roll 5 m
- Weight: 0,5 kg
- Black color
- Individual box. Grouping box 20 rolls. 300 rolls per pallet.

HANDLING AND STORAGE

The product should be protected from direct sunlight and be stored dry.



INSTALLATION

The best application temperature range is above +5 °C. Carefully cut the tiles to have a gap of 1 cm between both sides.

ONDULAIR SLIM has to be pressed on firmly after the application.

The overlapping between 2 rolls has to be at least 50 mm.

WARRANTY

Product durability is guaranteed for 10 years.

Color stability is guaranteed for 8 years.

All the claims will be considered with respect to application recommendations issued by Onduline company.

This TDS was made based on currently available information. Product was made in accordance with above mentioned parameters but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company.

www.onduline.co.uk

Onduline Building Products Ltd
Dawson House, 5 Jewry Street
London, UK, EC3N 2EX

Onduline®