

## Declaration of performance

Under the CPR EU 305/2011

**DOP M 2016 014**

1. Unique identification code of the product-type: **Ondutiss Air 95 , Air 95 T , Air 95 TT**
2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Flexible sheets for waterproofing – underlays for discontinuous roofing and wall cladding.**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
 

**Onduline SA**  
**35 rue Baudin**  
**92 300 Levallois Perret – France**  
**Tel : +33 1 55 63 80 10 Fax : +33 1 41 34 30 54**  
**www.onduline.com**
4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 3**
- 6.a. In case of the declaration of performance concerning a construction product covered by a harmonised standard : **EN13859-1: 2010 - EN 13859-2: 2010**
- 6.b. European Assessment document : **Not applicable**  
 European Technical Assessment : **Not applicable**  
 Notified Body : **Not applicable**
7. Declared performance

Essential characteristics	Performance	Appropriate technical documentation
Reaction to fire	E-d2	<b>EN13859-1 : 2010</b> <b>EN 13859-2 : 2010</b>
Water vapour transmission properties ( Sd in meter)	0,02 [+0,02 -0,005]	
Resistance to water penetration before artificial aging	Class W1	
Resistance to water penetration after artificial aging	Class W1	
Tensile strength Lengthwise before artificial ageing (N/50 mm)	210 ± 35	
Tensile strength Lengthwise after artificial ageing (N/50 mm)	190 ± 35	
Tensile strength Crosswise before artificial ageing (N/50 mm)	105 ± 20	
Tensile strength Crosswise after artificial ageing (N/50 mm)	90 ± 20	
Elongation Lengthwise before artificial ageing (%)	50 ± 30	
Elongation Lengthwise after artificial ageing (%)	40 ± 15	
Elongation Crosswise before artificial ageing (%)	70 ± 15	
Elongation Crosswise after artificial ageing (%)	45 ± 20	
Flexibility at low temperature	Passes at minus 40°C	
Resistance to tearing Lengthwise (N)	75 ± 30	
Resistance to tearing Crosswise (N)	90 ± 30	
Dangerous substances	None	

8. Appropriate Technical Documentation and/or Specific Technical documentation : **No**  
 The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Christophe ROHART**  
 R&D Director



Levallois-Perret, 25/04/16

rev.0