# **BARDOLINE® CLASSIC RECTANGULAR**

# **Material / Application**

BARDOLINE® CLASSIC RECTANGULAR is a colored bitumen shingle for roof and wall covering.

**(ETA 18-1036.** DOP N° 22 SA03

# **Benefits**

- Waterproofing
- Mechanical resistance
- Aesthetic
- Easy to install
- Durability
- Lightweight

# **Technical characteristics**

Length	EN 544	1000 (± 5) mm		
Width	EN 544	340 (± 3) mm		
Thickness		3 (± 5%) mm		
Weight		9,4 (± 10%) kg/m²		
Exposed Area		145 mm		
Min./max. pitch		14° - 85°*		
alid for I. and II. snow zone. For III. and more, please add 5°				

## PRODUCT PERFORMANCE

Mass of the fibreglass mat		100 (± 10%) g/m²
Granules single layer	EN 544	>1120 g/m²
Tensile strength MD / CD	EN 544	>600/400 N/50 mm
Tear resistance MD / CD (nail shank)	EN 544	>100 N
Elongation MD / CD		>2%
Granules adhesion	EN 544	<1,2 g
Asphalt	EN 544	>1000 g/m²

#### FIRE PERFORMANCE

External fire performance	EN 13501-5	F ROOF
Reaction to fire	EN 13501-1	E

# **Packaging**

Coverage / bundle	2,32 m <sup>2</sup>	3,05 m <sup>2</sup>
Shingles / bundle	16	21
Bundles / pallet	38	52
Useful m²/ pallet	88,16	158,6







# 1000 mm 340 mm 250 mm

#### Colors









Mixed Slate


Mixed Green

Mixed Brown

Mixed Red

# Storage

BARDOLINE® CLASSIC RECTANGULAR should be kept under dry conditions, protected from UV and heat as well as rain and moisture.



## **Warranty**

All the claims will be considered with respect to application recommendations issued by Onduline company.





## **Installation**

Special conditions of installation are required. Refer to the Installation Instructions.

#### FIRST STRIP






#### OTHER STRIPS



#### **HIPS AND RIDGES**





This TDS was made based on currently available information. The producer can update the technical data sheet without notice. Product was made in accordance with above mentioned parameters, but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/distributor recommendations and his needs.

