Technical data sheet

SA40 - V01 - 06-2022

ONDULINE® VENTILATED FOAM FILLER

Suitable for: ONDULINE® EASYFIX - ONDULINE® EASYSTYLE - ONDULINE® TILE - ONDULINE® DURO SX 35 - ONDULINE® STILO - ONDULINE® STILO 3D

Material / Application

Foam fillers used for small roofs (< 20 m²) covering annexe buildings.

VENTILATED FOAM FILLERS are sold as a kit, gathering fillers for the ridge and for the eave.

At the ridge, the foam filler is an essential component of the ridge system, to secure watertightness.

At the eave, the foam filler prevents birds, insects, or any other small animals to enter into the roof space.

The perforations in the foam provide sufficient ventilation for small non-residential buildings.

Technical characteristics

Material	Cross-linked polyethylene
Length	100,8 cm
Thickness	2,5 cm
Weight (pack 4 pcs)	0,11 kg
Height ridge filler	4 cm
Height eave filler	4 cm

PACKAGING

Pack	4 pcs (2 for ridge + 2 for eave)
Box	24 packs
Pallet	49 boxes

Handling and storage

The product should be protected from direct sunlight and be stored dry.

Warranty

Product durability is guaranteed for 10 years. All the claims will be considered with respect to application recommendations issued by Onduline company.


onduline.com

An Ondura Group Company
















Ridge

Color



Grey

Installation

At the eave, position the foam filler and fix them on the flat part with nails. Then fix the first row of sheets through the foam fillers.

At the ridge, position the foam fillers on both sides of the ridge line.

Apply the Ridge and fix it on each side of the roof, through the foam fillers, on top of the corrugations.

 $This\ TDS\ was\ made\ based\ on\ currently\ available\ information.\ Product\ was\ made\ in\ accordance$ with above mentioned parameters but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/ distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company.

