Technical data sheet

SA006 1103 12624 V3

ONDULINE® EASYFIX COMPACT

Material / Application

EN 534:2010 - Corrugated bitumen sheets Category S

DOP: 06-002 2016-12-12

(E

Technical characteristics

Longth (m)	L	100 cm	[-0.2;+1] cm
Length (m)	L	100 CIII	[-0.2 , +1] CIII
Width (m)	W	82 cm	± 1.5 cm
Thickness	t	2.6 mm	[+/-10 %]
Heigh of corrugation	Н	38 mm	± 2 mm
Pitch of corrugation	Р	96 mm	
Product surface		0.82 m ²	
Weight of product	(PPHR)	2.22 kg	± 0.16 kg
	(INTENSE)	2.26 kg	± 0.16 kg
Weight per sqm	(PPHR)	2.71kg m ²	[+/-10 %]
	(INTENSE)	2.76 kg m ²	[+/-10 %]
Nb of corrugations/flats		6 /5	
Useful surface		0.62 m ²	

MECHANICAL & PHYSICAL PROPERTIES

Bending under downward load	> 700 N/m ²
Impact strength	250 mm
Tearing strength	≥ 150 N
Water impermeability	Pass ¹
Proportion of bitumen	> 40%
Homogeneity	Pass ²
Water absorption	< 20%
Recycled content	50 % ³

DURABILITY

Water impermeability after agein	g Pass¹
Tearing strength after ageing	≥ 150 N
Thermal coefficient	< 100.10-6 1/K

¹No drop of water underneath sheet after 48 hours

FIRE PERFORMANCE

Reaction to fire - EN 13501-1	Е
External fire performance - EN 13501-5	Froof



Color


Intense colors





Intense Brown

Matte colors



Installation

Special conditions of installation are required. Refer to the installation guide.

Warranty

All the claims will be considered with respect to application recommendations issued by Onduline company, see terms and conditions.

Tariff code - HS: 68079000

This TDS was made based on currently available information. Product was made in accordance with above mentioned parameters, but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company. See terms and conditions: https://www.onduline.com/en/terms-and-conditions



²No area larger than 1 cm² without bitumen